

# **Technical data sheet**

EN361 EN355

The FALL SAFE® FS221 - ROOFWALKER HARNESS is a specifically designed harness for roof workers. It has a dorsal D-ring and 2 front loops for fall arrest attachment, an integrated energy absorber and a reflex fabric to keep user visible and safe. It has 2 side D-rings for work positioning, 6 point size adjustment for perfect fit and padded legs, all to give the user comfort and safety.

The airflow through all the harness layers is assured by the new and improved Croc 3.0 padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for use for several hours.

With reflective and extra breathable fabric, the FS221 combines the lightness of its composition with the FALL SAFE® quality assurance.

















S/M - 5605423570861 L/XL - 5605423570083 XXL - 5605423570885



STANDARDS

FN361 EN355

### SPECIFICATIONS

- -Croc padding 3.0 Air flow
- -PES webbing 45mm water repellent
- -Integrated energy absorber (side belt)
- -Aluminium 45º D-Ring at back/side
- -5 tool holders
- -4 aluminium IZY buckles
- -4 adjustment points
- -PA6 lanyard keepers
- -Fall indicator
- -twICEme® system tag

## PROPERTIES

MAX. RATED LOAD

140 Ka

MAX. SERVICE LIFE

S/M - 3.09 Kg L/XL - 3.11 Ka XXL - 3.14 Kg



































ARBORISM

RESCUE

ROPE ACCESS

TELECOM

**TOWER** 

CONFINED

RIGGERS

WIND **TURBINES** 

CONSTR

SCAFF

WOOD

PLATFORMS TACTICAL OFFSHORE

ROOF