


## FS222EVO

### ULTRA EVO HARNESS

EN361 EN358

The FALL SAFE® ULTRA EVO – FS222EVO it's a specifically designed to work at height, produced according to EN358:2018, EN361:2002 – maximum load up to 140kg. The ULTRA EVO HARNESS is equipped with 2 Side D-Rings for work positioning, 2 front loops for fall arrest, 1 back attachment aluminium ring ("A" Marking) ergonomic support belt, ergonomic backpad, padded legs, lanyard keepers, 6 point size adjustment for perfect fit and a reflective fabric to keep you visible and safer. The airflow through all the harness layers is assured by the new and improved Croc padding. This innovation also allows for a lighter and more ergonomic final product that is extremely comfortable for use for several hours. With reflective and extra breathable fabric, the FS222 combines the lightness of its composition with the FALL SAFE® quality assurance.



SIZE - EAN CODE	S/M - 5605423810059 L/XL - 5605423810066 XXL - 5605423810073	SPECIFICATIONS
INTENSITY OF USE		
STANDARDS	EN361 EN358	

- Croc padding 3.0 - Air flow
- PES webbing 45mm water repellent
- Aluminium 45° D-Ring at back/side
- Ergonomic front loop
- Block link connection
- 3 aluminium IZY buckles
- 5 adjustment points
- PA6 lanyard keepers
- Fall indicator
- twICEme® system tag

### PROPERTIES

MAX. RATED LOAD	140 Kg
MAX. SERVICE LIFE	10 years
SIZE   WEIGHT	S/M - 1.40 Kg L/XL - 1.50 Kg XXL - 1.60 Kg

### YOUR WORK OUR SOLUTION INDEX

