

# **Technical data sheet**

EN361

The FALL SAFE® FS242 - LITE HARNESS is the best selling ultra light harness. With low leg straps for improved comfort, this harness has an unique design and new impact resistant plates at its sides, to allow a comfortable fitting. The airflow through all the harness layers is assured by the new and improved Croc 3.0 padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for use for several hours.

With reflective and extra breathable fabric, the FS242 combines the lightness of its composition with the FALL SAFE® quality assurance.















S/M - 5605423570809 L/XL - 5605423570816 XXL - 5605423570823

INTENSITY OF USE



STANDARDS

### SPECIFICATIONS

- -PES webbing 45mm water repellent
- -Webbing loop at back/front
- -Croc padding 3.0 Air flow
- -4 tool holders points
- -2 aluminium IZY buckles
- -5 adjustment points
- -PA6 lanyard keeper
- -twICEme® system tag
- -Fall indicator

## PROPERTIES

MAX. RATED LOAD

140 Kg

MAX. SERVICE LIFE

S/M - 2.00 Kg L/XL - 2.10 Kg XXL - 2.20 Kg



































ARBORISM RESCUE

ROPE ACCESS

TELECOM

**TOWER** 

CONFINED

RIGGERS

WIND TURBINES

CONSTR

SCAFF

WOOD

PLATFORMS TACTICAL OFFSHORE

ROOF