

Technical data sheet

FS602

EDGE TESTED ANCHOR LINE

EN353-2 CNB/P/11.074

The FALL SAFE® FS602 - SHARP EDGE ANCHOR LINE is equipped with 1 hook to connect into anchor point on structure and other to connect to front or dorsal D-Ring attachment on full body harness, fall protection vest or fall protection overall. It has a grab-on stainless steel fall arrester with automatic locking. FS602 was tested in a horizontal application, over a sharp edge (r 0.5mm).



























5M - 5605423321135 10M - 5605423320947 20M - 5605423320923 Other sizes on request

N/A

STANDARDS

EN353-2 CNB/P/11.074

SPECIFICATIONS

- -Aluminium rope grab
- -PES energy absorber
- -Aluminium karabiner included
- -PA static rope 12mm
- -PA6 rope protector

PROPERTIES

MAX. RATED LOAD

120 Kg

MAX. SERVICE LIFE

10 years

5M - 0.90 Kg 10M - 1.20 Kg 20M - 2.50 Kg

































ARBORISM RESCUE

ROPE ACCESS

TELECOM

TOWER

CONFINED RIGGERS

WIND TURBINES

CONSTR

SCAFF

WOOD

PLATFORMS TACTICAL OFFSHORE

ROOF