

FAST-ACT® 400G PRESSURIZED CYLINDER



FA015-0400-00NS



Disposable type

Product Details:

- 1 Plastic valve for controlled discharge
- 2 Safety clip
- 3 Aluminum lightweight body
- 4 400g FAST-ACT® powder
- 5 Easy to follow visual instructions
- 6 Mounting bracket

No formal maintenance required

MEDIUM FAST-ACT Powder

PROPELLANT Nitrogen Gas

FILLED WEIGHT (with bracket) 100% RAYON

USAGE TEMPERATURE -20°C to +50°C

AVERAGE DISCHARGE TIME 9.9 seconds
Ambient

RANGE OF DISCHARGE 2-3 meters

CAPACITY 400g

WORKING PRESSURE 140psig at 54.4°C
(124psig at Ambient)

HOW TO USE:


1

Hold upright and remove safety clip.




2

Aim the nozzle at hazard.



3

Press the trigger down firmly to apply treatment.



VAPOR

For vapor hazard, spray into air in direction of hazard.



LIQUID

For liquid hazard, spray on spill to ensure complete coverage of hazard.



- **Minimal Training Required** All units are ready-to-use, no premixing or preparation.
- **Fast** Immediately neutralizes, adsorbs or contains on contact
- **Safe** Non-toxic, non-corrosive, non-flammable, environmentally friendly