

PRODUCT NUMBER: 1033464
TurboLite EDGE 2m Web
Twistlock+swivel Scaffhook

Miller TurboLite Edge tested self retracting lifeline with Twistlock Aluminium karabiner and scaff hook 60 mm with integrated swivel.



Översikt

Reference Number

1033464

Product Type

Fallskydd

Range

Fall Arrest Blocks and Winches

Brand

Miller by Honeywell

Industry

- Industry
- Building and Construction
- Iron and steel industry
- Maintenance
- Telecoms
- Utilities

Product Use

The Miller TurboLite Edge is a lightweight edge-tested self-retracting lifeline for all work situations, including those that require the possibility to connect at foot level when working on the edge. It is certified at 140 kgs and approved to be attached at foot level.

Ideal for construction (scaffold erecting/dismantling, steel erecting,...), general industries (maintenance) and utilities (wind, power & telecom: work on pylons), oil & gas.

Features & Benefits

Feature

Housing: impact resistant nylon Braking system: stainless steel Pulley: polypropylene & aluminium Webbing: polyester envelop & Vectran® core (25.4mm x 1.5mm) Polyamide shock absorber maxi length when full deployed: 1.75 m Retracted length : 790 mm Extended length : 2000 mm Max. rated Load: 140 kg Breaking strength: > 1700 DaN. Certified to the following standards: EN 360: 2002 VG11.062 (140 kg) VG11.085 (FF2) VG11.060 (edge-tested) Temperature of use: from -50°C to +60°C

Benefit

One product fits all work situations o Product adapted to all fall factors: FF0, FF1 & FF2 o Edge-tested product thanks to reinforced webbing: horizontal use possible without restrictions. o Product tested at 140 kg (even in FF2 "foot level" anchorage) Comfort and freedom of movement o Lightweight SRL: 1 Kg (SRL with 2 twist-lock karabiners) o 2 swivels

(on anchorage connection karabiner & housing) avoids twist effect of the webbing and improves the ability of the webbing to retract Greater safety o Easy visual inspection thanks to the integrated fall indicator

Technical Description

External

Connectors

Karabiners: Twistlock carabiner (opening: 18mm) raw material: aluminium Swivel Scaff Hook (opening: 60mm) raw material: aluminium with integrated swivel

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

EC Attestation

EC Attestation Number

0082/490/160/03/15/0074 ext n° 01/10/15

Certifications

- Other VG11.062 (140 kg)
- Other VG11.085 (FF2)
- Other VG11.060 (edge-tested)

Ytterligare information

User Manual

User Information Sheet

User manual

Maintenance

Life Cycle

Life expectancy of our harnesses is 10 years from the date of manufacture.

Storage Information

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Care Instructions

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.


Packaging

EAN Code

3660681058386

Country of Origin

France



Miller TurboLite™ edge

**EDGE
TESTED**

Description:

A lightweight edge-tested self-retracting lifeline for all work situations, including those that require the possibility to connect at foot level when working on the edge.

Ideal for construction (scaffold erecting/dismantling, steel erecting,...), general industries (maintenance) and utilities (wind, power & telecom: work on pylons), oil & gas.

Available in various combinations of karabiners with integrated swivel.

Benefits:

One product fits all work situations

- Product adapted to all fall factors: FF0, FF1 & FF2
- Edge-tested product thanks to reinforced webbing: horizontal use possible without restrictions.
- Product tested at 140 kg (even in FF2 “foot level” anchorage)

Comfort and freedom of movement

- Lightweight SRL: 1 Kg (SRL with 2 twist-lock karabiners)
- 2 swivels (on anchorage connection karabiner & housing) avoids twist effect of the webbing and improves the ability of the webbing to retract







Greater safety

- Easy visual inspection thanks to the integrated fall indicator



Features:

Ref.	Harness connection	Picture	Anchorage connection	Max. length (m)	Weight (kg)
1033464	Aluminium twist-lock karabiner, opening 18mm		Aluminium scaff hook 60mm with integrated swivel	2	1.4
1033465	Aluminium twist-lock karabiner, opening 18mm		Aluminium swivel twist-lock karabiner, opening 21 mm	2	1.06
1033466	Aluminium twist-lock karabiner, opening 18mm		Aluminium scaff hook GO60 with integrated swivel, opening 60 mm	2	1.2
1033467	∅		∅	1.80	0.84

Housing: impact resistant nylon

Braking system: stainless steel

Pulley: polypropylene & aluminium

Webbing: polyester envelop & Vectran® core (25.4mm x 1.5mm)


Polyamide shock absorber maxi length when full deployed: 1.75 m

Max. rated Load: 140 kg

Breaking strength: > 1700 DaN.

Certified to the following standards: EN 360: 2002
 VG11.062 (140 kg)
 VG11.085 (FF2)
 VG11.060 (edge-tested)

Temperature of use: from -50°C to +60°C



LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com



E.C. Declaration of Conformity

The manufacturer or its legal representative supplier in the European Community:

Honeywell Safety Products Europe

Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:

Designation: TurboLite EDGE 2m Web Twistlock+swivel Scafhook

Reference: 1033464

Standard(s): EN360

This PPE is the object of the below EC examination certificate n°:

Och är underställt proceduren som beskrivs i artikel 11 punkt B i kommissionens direktiv 89/686/EG under tillsyn av nedan kungjorda organ.

Levererad av:

APAVE SUDEUROPE SAS

BP 3

33370

ARTIGUES près BORDEAUX

France

Upprättat i Vierzon, on the 20/06/2016

Av: Frederic Wagner

Avdelning: Fallskydd

ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

www.honeywellsafety.com