

# SIANK

## ANCHOR POINT FOR STANDING SEAM METAL ROOFS

### EFFICIENT

The system is fixed to a single seam of the sheet using a few tools.

### UNOBTRUSIVE

Device fixed to the seam by means of a single clamp, without the need to drill holes in the metal sheet, guaranteeing its impermeability and durability.



LOAD DIRECTION




TYPES OF APPLICATION



VIDEO




MANUALS



## TECHNICAL DATA\*

substructure	minimum thickness
 Fe	0,5 mm
 Al	0,7 mm
 Cu	0,5 mm

substructure	minimum thickness
 Zn - Ti	0,7 mm
 stainless steel	0.4 mm

\* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

## CODES AND DIMENSIONS

CODE	description	material	B [mm]	H [mm]	L [mm]	pcs
SIANK	anchor point for seaming 25 mm	AISI 304 stainless steel grade 1.4301	163	130	400	1
SIANK65	anchor point for seaming 65 mm	AISI 304 stainless steel grade 1.4301	104	163	400	1
SIANKA	anthracite-colour anchorage point for seaming 25 mm	AISI 304 stainless steel grade 1.4301	163	130	400	1
SIANKB	brown anchorage point for seaming 25 mm	AISI 304 stainless steel grade 1.4301	163	130	400	1

